

the label directions, each quart of the reconstituted product shall contain 400 International Units thereof.

(c) *Dry whole milk.* The pasteurized product resulting from the removal of water from milk and contains the lactose, milk proteins, milk fat, and milk minerals in the same relative proportions as in the fresh milk from which made. The milk may be standardized but shall not contain buttermilk, or any added preservative, neutralizing agent or other chemicals.

(d) *Dry buttermilk.* The product resulting from drying liquid buttermilk that was derived from the churning of butter and pasteurized prior to condensing at a temperature of 161 °F for 15 seconds or its equivalent in bacterial destruction. Dry buttermilk shall have a protein content of not less than 30.0 percent. Dry buttermilk shall not contain nor be derived from nonfat dry milk, dry whey, or products other than buttermilk, and shall not contain any added preservative, neutralizing agent, or other chemical.

(e) *Dry buttermilk product.* The product resulting from drying liquid buttermilk that was derived from the churning of butter and pasteurized prior to condensing at a temperature of 161 °F for 15 seconds or its equivalent in bacterial destruction. Dry buttermilk product has a protein content less than 30.0 percent. Dry buttermilk product shall not contain nor be derived from nonfat dry milk, dry whey, or products other than buttermilk, and shall not contain any added preservative, neutralizing agent, or other chemical.

[40 FR 47911, Oct. 10, 1975. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981, as amended at 56 FR 33855, July 24, 1991; 61 FR 17548, Apr. 22, 1996; 61 FR 35590, July 8, 1996]

ROOMS AND COMPARTMENTS

§ 58.210 Dry storage of product.

Storage rooms for the dry storage of product shall be adequate in size, kept clean, orderly, free from rodents, insects, and mold, and maintained in good repair. They shall be adequately lighted and ventilated. The ceilings, walls, beams and floors should be free from structural defects and inaccessible

false areas which may harbor insects.

§ 58.211 Packaging room for bulk products.

A separate room or area shall be provided for filling bulk containers, and shall be constructed in accordance with § 58.126. The number of control panels and switch boxes in this area should be kept to a minimum. Control panels shall be mounted a sufficient distance from the walls to facilitate cleaning or satisfactorily sealed to the wall, or shall be mounted in the wall and provided with tight fitting removable doors to facilitate cleaning. An adequate exhaust system shall be provided to minimize the accumulation of product dust within the packaging room and where needed, a dust collector shall be provided and properly maintained to keep roofs and outside areas free of dry product. Only packaging materials that are used within a day's operation may be kept in the packaging area. These materials shall be kept on metal racks or tables at least six inches off the floor. Unnecessary fixtures, equipment, or false areas which may collect dust and harbor insects, should not be allowed in the packaging room.

§ 58.212 Hopper or dump room.

A separate room shall be provided for the transfer of bulk dry dairy products to the hoppers and conveyors which lead to the fillers. This room shall meet the same requirements for construction and facilities as the bulk packaging operation. Areas and facilities provided for the transfer of dry dairy products from portable bulk bins will be accepted if gasketed surfaces or direct connections are used that appreciably eliminate the escape of product into the area.

§ 58.213 Repackaging room.

A separate room shall be provided for the filling of small packages and shall meet the same requirements for construction and facilities as the bulk packaging operation.